

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-236916

(43)Date of publication of application : 13.09.1996

(51)Int.Cl.

H05K 3/34  
B23K 3/06  
H01L 21/321

(21)Application number : 07-041759

(71)Applicant : FUJITSU LTD  
FUJITSU VLSI LTD

(22)Date of filing : 01.03.1995

(72)Inventor : KADOWAKI TETSUJI


## (54) METHOD AND DEVICE FOR MOUNTING SOLDER BALL

### (57)Abstract:

**PURPOSE:** To make container inverting operations unnecessary so as to shorten the cycle time of solder ball mounting operations by supplying solder balls to pads in a state where the solder balls are arranged in corresponding to the arrangement of the pads.

**CONSTITUTION:** A container 31 contains solder balls 40 and a solder ball arranging and supplying device 32 is provided at the bottom of the container 31 and supplies the solder balls 40 to pads from the bottom of the container 31 in a state where the solder balls 40 are arranged in corresponding to the arrangement of the pads. A solder ball arranging state inspecting means 35 inspects whether or not the solder balls 40 are properly arranged.

Therefore, a mounting error, the absence of a solder ball on a pad, can be prevented. A lift device 37 elevates or lowers the container 31 and device 32 against a substrate positioning table 38. The table 38 positions the substrate of an LSI package.



### LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]